



Bent edge



Panel without grommet hole easy for wire



Panel without grommet hole

## Specifications

### General information

- Panel weight: 23.15lbs./10.5kg bare.
- 1-3/8 inches deep with no covering.
- All steel welded construction.
- Protected from corrosion by an epoxy paint finish.
- Class A flame spread rating.
- Non-combustible material.

## Understructure Options

- Freestanding
- Posilock2'
- Bolted Stringer
- 4' Bolted Stringer

## Covering Options

For additional laminate options contact Inside Sales

Bare Painted Panel Options

- Bare Painted Finish to accept carpet tile application
- Bare Painted Finish to accept PosiTile application

concentrated load			impact load N	ultimate load N	uniform load N/m <sup>2</sup>	rolling load	
LB	N	KG				10times	1000times
≥440	≥1960	≥200	≥295	≥5880	≥9720	≥1958	≥1566
≥662	≥2950	≥301	≥445	≥8850	≥12500	≥2948	≥2356
≥800	≥3550	≥363	≥538	≥11250	≥16100	≥3560	≥2670
≥1000	≥4450	≥453	≥670	≥13350	≥23000	≥4450	≥3560
≥1250	≥5560	≥567	≥670	≥16680	≥33000	≥5560	≥4450
≥1500	≥6660	≥680	≥780	≥26690	≥43000	≥6670	≥5560
≥2000	≥8880	≥906	≥780	≥31130	≥58000	≥8800	≥8000

1. System Design Load is based on permanent set «0.010" and is verified by loading panels in accordance with the Cisca concentrated load method but with panels installed on actual understructure instead of steel blocks. (Testing on blocks does not represent performance of an actual installation.) Ultimate, Rolling, and Impact Load tests are performed using Cisca test procedures.

2. Safety Factor is Ultimate Load divided by Design Load.